

FLOODPLAIN MANAGEMENT ORDINANCE

A. PURPOSE & ESTABLISHMENT

Certain areas of Newcastle are subject to periodic flooding, causing serious damage to properties within these areas. Relief is available in the form of flood insurance as authorized by the National Flood Insurance Act of 1968.

Therefore, the Town of Newcastle, Maine has chosen to become a participating community in the National Flood Insurance Program and agrees to comply with the requirements of the National Flood Insurance Act of 1968 (P.L. 90-488, as amended) as delineated in this chapter on Floodplain Management Ordinance.

It is the intent of the Town to require the recognition and evaluation of flood hazards in all official actions relating to land use in the floodplain areas having special flood hazards.

The Town of Newcastle has the legal authority to adopt land use and control measures to reduce future flood losses pursuant to Title 30-A MRSA, Sections 3001-3007, 4352, 4401-4407 and Title 38 MRS, Section 440.

The National Flood Insurance Program, established in the aforesaid Act, provides that areas of the Town of Newcastle having a special flood hazard be identified by the Federal Emergency Management Agency and that floodplain management measures be applied in such flood hazard areas. This ordinance establishes a Flood Hazard Development Permit system and review procedures for development activities in the designated flood hazard areas of the Town of Newcastle, Maine.

The areas of special flood hazard, are identified by the Federal Emergency Management Agency in a map entitled "Flood Insurance Rate Map – Town of Newcastle, Maine Lincoln County" (page 1 of 2) and (page 2 of 2) dated May 17, 1977) which is hereby adopted by reference and declared to be part of this ordinance.

B. PERMIT REQUIRED

Before any construction or other development (as defined in Section E of the Floodplain Management Ordinance) including the placement of manufactured homes, begins within any areas of special flood hazard established in Section A of Floodplain Management Ordinance, a Flood Hazard Development Permit shall be obtained from the Code Enforcement Officer (CEO) except as provided in Section H of Floodplain Management Ordinance. This permit is in addition to any other building permits which may be required pursuant to the codes and ordinances of the Town of Newcastle, Maine.

C. APPLICATION FOR PERMIT

The application for a Flood Hazard Development Permit shall be submitted to the Code Enforcement Officer and shall include:

Approved: November 3, 2020

Effective: January 1, 2021

1. The name, address and phone number of the applicant, owner and contractor;
2. An address and a map indicating the location of the construction site;
3. A site plan showing location of existing and/or proposed development, including but not limited to structures, sewage disposal facilities, water supply facilities, areas to be cut and filled and lot dimensions;
4. A statement of the intended use of the structure a/or development;
5. A statement of the cost of development including all materials and labor;
6. A statement as to the type of sewage system proposed;
7. Specifications of dimensions of the proposed structure and/or development;
(Items C. 8-11. B. applies only to new construction and substantial improvements.)
8. The elevation in relation to the National Geodetic Vertical Datum (NGVD) or to a locally established datum of the:
 - a. Base Flood at the proposed site of all new or substantial improved structures, which in Zone A is determined:
 - (1) From any base flood elevation data from federal, state or other technical sources (such as FEMA's Quick-2 model, FEMA 265/July 1995), including information obtained pursuant to Section G.10 and J.4;
 - (2) From the contour elevation extrapolated from a best fit analysis of the floodplain boundary when overlaid onto a USGS Quadrangle Map or other topographic map prepared by a Professional Land Surveyor or registered professional engineer, if the floodplain boundary has a significant correlation to the elevation contour line(s); or, in the absence of all other data,
 - (3) To be the elevation of the ground at the intersection of the floodplain boundary and a line perpendicular to the shoreline which passes along the ground through the site of the proposed building.
 - b. Highest and lowest grades at the site adjacent to the walls of the proposed building;
 - c. Lowest floor, including basement; and whether such structures contain a basement; and,

- d. Level, in the case of non-residential structures only, to which the structure will be flood proofed;
- 9. A description of an elevation reference point established on the site of all developments for which elevation standards apply as required in Section G of this Floodplain Management Ordinance
- 10. A written certification by a Professional Land Surveyor, registered professional engineer or registered professional architect, that the base flood elevation and grade elevations shown on the application are accurate;
- 11. The following certifications as required in Section G of this Floodplain Management Ordinance by a registered professional engineer or registered Professional architect:
 - a. A Flood Proofing Certificate (FEMA Form 81-65, 01/03, as amended), to verify that the flood proofing methods for any non-residential structures will meet the flood proofing criteria of Section C.8.D.; Section G.7.; and other applicable standards in Section G;
 - b. A hydraulic Openings Certificate to verify that engineered hydraulic openings in foundation walls will meet the standards of Section G.11.B.1.;
 - c. A certified statement that bridges will meet the standards of Section G.12.;
 - d. A certified statement that containment walls will meet the standards of Section G.13;
- 12. A description of the extent to which any water course will be altered or relocated as a result of the proposed development; and,
- 13. A statement of construction plans describing in detail how each applicable development standard in Section G will be met.

D. APPLICATION FEE AND EXPERT'S FEE

A non-refundable application fee of \$25.00 for all minor development and \$50.00 for all new construction or substantial improvements shall be paid to the Town Clerk and a copy of a receipt for the same shall accompany the application.

If the Code Enforcement Officer and/or Board of Appeals needs the assistance of a professional engineer or another expert, an additional fee may be charged. An expert shall not be hired by the municipality at the expense of an applicant until the applicant has either consented to such hiring in writing or been given an opportunity to be heard on the subject. An applicant who is dissatisfied with a decision to hire expert assistance may appeal that decision to the Board of Appeals. The expert's fee shall be paid in full by the applicant in advance, before the expert commences work.

Approved: November 3, 2020

Effective: January 1, 2021

Failure to pay the bill shall constitute a violation of the ordinance and be grounds for the issuance of a stop work order.

E. DEFINITIONS

Unless specifically defined below, words and phrases used in this Ordinance shall have the same meaning as they have at common law and to give this ordinance its most reasonable application. Words used in the present tense include the future, the singular number includes the plural and the plural number includes the singular.

The word “may” is permissive; “shall” is mandatory and not discretionary.

Accessory Structure – Means a small detached structure that is incidental and subordinate to the principal structure.

Adjacent grade – Means the natural elevation of the ground surface prior to construction next to the proposed walls of a structure.

Area of Special Flood Hazard – Means the land in the floodplain having a one percent or greater chance of flooding in any given year, as specifically identified in the Flood Insurance Rate Map cited in Section A of this ordinance.

Base Flood – Means the flood having a one percent chance of being equaled or exceeded in any given year, commonly called the 100-year flood.

Basement – Means any area of the building having its floor sub grade (below ground level) on all sides.

Building – See **Structure**.

Certificate of Compliance - A document signed by the Code Enforcement Officer stating that a structure is in compliance with all of the provisions of this ordinance.

Code Enforcement Officer – A person certified under Title 30-A MRSA, Section 4451 (including exceptions in subsection 4451, paragraph 1) and employed by a municipality to enforce all applicable comprehensive planning and land use laws and ordinances.

Conditional Use – Means a use that because of its potential impact on surrounding areas and structures, is permitted only upon review and approval by the Planning Board pursuant to Section H.

Development – Means any man-made change to improved or unimproved real estate, including but not limited to buildings or other structures, mining, dredging, filling, grading, paving, excavation, drilling operations or storage of equipment or materials.

Elevated Building – Means a non-basement building:

- a. Built, in the case of a building in Zone A, to have the top of the elevated floor, elevated above the ground level by means of pilings, columns, posts, piers, or "stilts"; and,
- b. Adequately anchored so as not to impair the structural integrity of the building during a flood of up to one foot above the magnitude of the base flood.

In the case of Zone, A, **Elevated Building** also includes a building elevated by means of fill or solid foundation perimeter walls hydraulic openings sufficient to facilitate the unimpeded movement of flood waters, as required in Section G.11.

Elevation Certificate - An official form (FEMA Form 81-31, 02/06, as amended) that:

- a. Is used to verify compliance with the floodplain management regulations of the National Flood Insurance Program; and,
- b. Is required for purchasing flood insurance.

Flood or Flooding – Means:

- a. A general and temporary condition of partial or complete inundation of normally dry land areas from:
 - (1) The overflow of inland or tidal waters.
 - (2) The unusual and rapid accumulation or runoff of surface waters from any source.
- b. The collapse or subsidence of land along the shore of a lake or other body of water as a result of erosion or undermining caused by waves or currents of water exceeding anticipated cyclical levels or suddenly caused by an unusually high-water level in a natural body of water, accompanied by a severe storm, or by an unanticipated force of nature, such as a flash flood or an abnormal tidal surge, or by some similarly unusual and unforeseeable event which results in flooding as defined in paragraph a.1 of this definition.

Flood Elevation Study – Means an examination, evaluation and determination of flood hazards and, if appropriate, corresponding water surface elevations.

Flood Insurance Rate Map (FIRM) – Means an official map of a community, on which the Federal Insurance Administrator has delineated both the special hazard areas and the risk premium zones applicable to the community.

Floodplain or Flood-prone Area – Means any land area susceptible to being inundated by water from any source (see flooding).

Floodplain Management – Means the operation of an overall program of corrective and preventive measures for reducing flood damage, including but not limited to emergency preparedness plans, flood control works, and floodplain management regulations.

Floodplain Management Regulations – Means zoning ordinances, subdivision regulations, building codes, health regulations, special purpose ordinances (such as a floodplain ordinance, grading ordinance, and erosion control ordinance) and other applications of police power. The term describes such state or local regulations, in any combination thereof, which provide standards for the purpose of flood damage prevention and reduction.

Flood proofing – Means any combination of structural and non-structural additions, changes, or adjustments to structures which reduce or eliminate flood damage to real estate or improved real property, water and sanitary facilities, structures and contents.

Floodway - See **Regulatory Floodway**.

Freeboard – Means a factor of safety usually expressed in feet above a flood level for purposes of floodplain management. Freeboard tends to compensate for the many unknown factors, such as wave action, bridge openings, and the hydrological effect of urbanization of the watershed that could contribute to flood heights greater than the height calculated for a selected size flood and floodway conditions.

Functionally Dependent Use – Means a use which cannot perform its intended purpose unless it is located or carried out in close proximity to water. The term includes only docking facilities, port facilities that are necessary for the loading and unloading of cargo or passengers, and ship building and ship repair facilities, but does not include long-term storage or related manufacturing facilities.

Historic Structure – Means any structure that is:

- a. Listed individually in the National Register of Historic Places (a listing maintained by the Department of Interior) or preliminarily determined by the Secretary of the Interior as meeting the requirements for individual listing on the National Register;
- b. Certified or preliminarily determined by the Secretary of the Interior as contributing to the historical significance of a registered historic district or a district preliminarily determined by the Secretary of the Interior to qualify as a registered historic district;
- c. Individually listed on a state inventory of historic places in states with

historic preservation programs which have been approved by the Secretary of the Interior; or

d. Individually listed on a local inventory of historic places in communities with historic preservation programs that have been certified either:

(1) By an approved State program as determined by the Secretary of the Interior, or

(2) Directly by the Secretary of the Interior in states without approved programs.

Locally Established Datum – means for the purpose of this ordinance, an elevation established for a specific site to which all other elevations at the site are referenced. This elevation is generally not referenced to the National Geodetic Vertical Datum (NGVD) or any other established datum and is used in areas where Mean Sea Level data is too far from a specific site to be practically used.

Lowest Floor – Means the lowest floor of the lowest enclosed area (including basement). An unfinished or flood resistant enclosure, usable solely for parking of vehicles, building access or storage in an area other than a basement area is not considered a building's lowest floor, provided that such enclosure is not built so as to render the structure in violation of the applicable non-elevation design requirements described in Section G.11 of this ordinance.

Manufactured Home – Means a structure, transportable in one or more sections, which is built on a permanent chassis and is designed for use with or without a permanent foundation when connected to the required utilities. For floodplain management purposes the term manufactured home also includes park trailers, travel trailers and other similar vehicles placed on a site for greater than 180 consecutive days.

Manufactured Home Park or Subdivision – Means a parcel (or contiguous parcels) of land divided into two or more manufactured home lots for rent or sale.

Mean Sea Level – Means, for purposes of the National Flood Insurance Program, the National Geodetic Vertical Datum (NGVD) of 1929, or other datum, to which base flood elevations shown on a community's "Flood Insurance Rate Map" are referenced.

Minor Development – Means all development that is not new construction or a substantial improvement, such as repairs, maintenance, renovations, or additions, whose value is less than 50% of the market value of the structure. It also includes, but is not limited to: accessory structures as provided in Section G.9., mining, dredging, filling, grading, paving, excavation, drilling operations, storage or equipment or materials, deposition or extraction of materials, public or private sewage disposal systems or water supply facilities that do not involve structures; and nonstructural projects such as bridges, dams, towers, fencing, pipelines, wharves and piers.

National Geodetic Vertical Datum (NGVD) – Means the national vertical datum, whose standard was established in 1929, which is used by the National Flood Program (NFIP). NGVD was based upon mean sea level in 1929 and has been called “1929 Mean Sea Level (MSL).”

New Construction – Means structures for which the “start of construction” commenced on or after the effective date of the initial floodplain management regulations adopted by a community and includes any subsequent improvements to such structures.

100 Year Flood - See **Base Flood**.

Regulatory Floodway - The floodway which is:

- a. Means the channel of a river or other water course and the adjacent land areas that must be reserved in order to discharge the base flood without cumulatively increasing the water surface elevation more than one foot, and
- b. In Zone A areas, the floodway is the channel of a river or other water course and the adjacent land areas to a distance of one-half the width of the floodplain, as measured from the normal high-water mark to the upland limit of the floodplain.

Riverine – Means relating to, formed by, or resembling a river (including tributaries), stream or brook, etc.

Special flood Hazard Area - see **Area of Special Flood Hazard**.

Start of Construction – Means the date the building permit was issued, provided the actual start of construction, repair, reconstruction, rehabilitation, addition, placement, substantial improvement or other improvement was within 180 days of the permit date. The actual start means either the first placement of permanent construction of a structure on a site, such as the pouring of slab or footings, the installation of piles, the construction of columns, or any work beyond the stage of excavation; or the placement of a manufactured home on a foundation. Permanent construction does not include land preparation, such as clearing, grading and filling; nor does it include the installation of streets and/or walkways; nor does it include excavation for basement, footings, piers, or foundations or the erection of temporary forms; nor does it include installation on the property of accessory buildings, such as garages or sheds not occupied as dwelling units or not part of the main structure. For a substantial improvement, the actual start of construction means the first alteration of any wall, ceiling, floor, or other structural part of a building, whether that alteration affects the external dimensions of the building.

Structure – Means, for floodplain management purposes, a walled and roofed building. A gas or liquid storage tank that is principally above ground is also a structure.

Substantial Damage – Means damage of any origin sustained by a structure whereby the cost of restoring the structure to it before damage condition would equal or exceed 50 percent of the market value of the structure before the damage occurred.

Substantial Improvement – Means any reconstruction, rehabilitation, addition, or other improvement of a structure, the cost of which equals or exceeds 50 percent of the market value of the structure before the start of construction of the improvement. This term includes structures which have incurred substantial damage, regardless of the actual repair work performed. The term does not, however, include either:

- a. Any project for improvement of a structure to correct existing violations of state or local health, sanitary, or safety code specifications which have been identified by the local code enforcement official and which are the minimum necessary to assure safe living conditions; or,
- b. An alteration of an Historic Structure provided that the alteration will not preclude the structures' continued designation as an historic structure, and a variance is obtained from the community's Board of Appeals.

Variance – Means a grant of relief by a community from the terms of a floodplain management regulation.

Violation – Means the failure of a structure or development to comply with a community's floodplain management regulations.

F. REVIEW STANDARDS FOR FLOOD HAZARD DEVELOPMENT PERMIT APPLICANTS

The Code Enforcement Officer shall:

1. Review all applications for the Flood Hazard Development Permit to assure that proposed developments are reasonably safe from flooding and to determine that all pertinent requirements of Section G (Development Standards) have been, or will be met;
2. Utilize, in the review of all Flood Hazard Development Permit applications:
 - a. The Base Flood data contained in the "Flood Insurance Rate map – Town of Newcastle, Maine," as described in Section A.
 - b. In special flood hazard areas where base flood elevation and floodway data are not provided, the Code Enforcement Officer shall obtain, review and reasonably utilize any base flood elevation and floodway data from federal, state, or other technical sources, including information obtained

pursuant to Section C.8.A.; Section G.10; and Section J.4 of this ordinance; and

- c. When the community establishes a base flood elevation in Zone A by methods outlined in Section C.8.A.2., the community shall submit that data to the Maine Floodplain Management Program in the State Planning Office.
3. Make interpretations of the location of boundaries of special flood hazard areas shown on the maps described in Section A of this ordinance;
4. In the review of Flood Hazard Development Permit applications, determine that all necessary permits have been obtained from those federal, state, and local government agencies from which prior approval is required by Federal Water Pollution Control Act Amendments of 1972, 33 USC 1334;
5. Notify adjacent municipalities, the Department of Environmental Protection and the Maine Floodplain Management Program in the State Planning Office prior to any alteration or relocation of a water course and submit copies of such notifications to the Federal Emergency Management Agency;
6. If the applicant satisfies the requirements of this ordinance, approve the issuance of one of the following Flood Hazard Development Permit based on the type of development:
 - a. A two-part Flood Hazard Development Permit for elevated structures. Part I shall authorize the applicant to build a structure to and including the first horizontal floor only above the base flood level. At that time, the applicant shall provide the Code Enforcement Officer with an Elevation Certificate completed by a Professional Land Surveyor, registered professional engineer or a registered professional architect based on Part 1 permit construction, "as built", for verifying compliance with the elevation requirements of Section G, paragraphs 6, 7 and 8. Following review of the Elevation Certificate data, which shall take place within 72 hours of receipt of the application, the Code Enforcement Officer shall issue Part II of the Flood Hazard Development Permit. Part II shall authorize the applicant to complete the construction project; and,
 - b. A Flood hazard Development Permit for Flood proofing of Non-Residential Structures that are new construction or substantially improved non-residential structures that are not being elevated but that meet the flood proofing standards of Section G.7.A., B. and C. The applicant for this permit shall include a Flood proofing Certificate signed by a registered professional engineer or registered professional architect; or,
 - c. A Flood Hazard Development Permit for Minor Development if for all development that is not new construction or a substantial improvement, such

as repairs, maintenance, renovations, or additions, whose value is less than 50% of the market value of the structure. Minor development also includes, but is not limited to accessory structures as provided for in Section G.9., mining, dredging, filling, grading, paving, excavation, drilling operations, storage of equipment or material, deposition or extraction of materials, public or private sewage disposal systems or water supply facilities that do not involve structures; and non-structural projects such as bridges, dams, towers, fencing, pipelines, wharves and piers.

For development that requires review and approval as a Conditional Use, as provided for in this ordinance, the Flood Hazard Development Permit Application shall be acted upon by the Planning Board as required in Section H.

7. Maintain, as a permanent record, copies of all Flood Hazard Development Permit Applications, corresponding Permits issued, and data relevant thereto, including reports of the Board of Appeals on variances under the provisions of Section K of this ordinance, and copies of Elevation Certificates, Flood proofing Certificates, Certificates of Compliance and certificates of design standards required under the provisions of Section C, G and I of this ordinance.

G. DEVELOPMENT STANDARDS

All developments in areas of special flood hazard shall meet the following applicable standards:

1. All Development – All development shall:

- a. Be designed or modified and adequately anchored to prevent flotation, (excluding piers and docks), collapse or lateral movement of the development resulting from hydrodynamic and hydrostatic loads, including the effects of buoyancy;
- b. Use construction materials that are resistant to flood damage;
- c. Use construction methods and practices that will minimize flood damage; and,
- d. Use electrical, heating, ventilation, plumbing, and air conditioning equipment, and other service facilities that are designed and/or located to prevent water from entering or accumulating within the components during flooding conditions.

2. Water Supply – All new and replacement water supply systems shall be designed to minimize or eliminate infiltration of flood waters into the systems.

3. Sanitary Sewage Systems - New and replacement sanitary sewage systems shall be designed and located to minimize or eliminate infiltration of flood waters into the system and discharges from the system into flood waters.

4. **On-Site Waste Disposal Systems** - On site waste disposal systems shall be located and constructed to avoid impairment to them or contamination from them during floods.
5. **Water Carrying Capacity** – All development associated with altered or relocated portions of a watercourse shall be constructed and maintained in such a manner that no reduction occurs in the flood carrying capacity of any watercourse.
6. **Residential** - New construction or substantial improvement of any residential structure located within Zone A shall have the lowest floor (including basement) elevated to at least one foot above the base flood elevation utilizing information obtained pursuant to Section C.8.A.; Section F.2; or Section J.4.
7. **Non Residential** - New construction or substantial improvement of any non-residential structure located within Zone A shall have the lowest floor (including basement) elevated to at least one foot above the base flood elevation utilizing information obtained pursuant to Section C.8.1.; Section F.2; or Section J.4., or together with attendant utility and sanitary facilities shall:
 - a. Be flood proofed to at least one foot above the base flood elevation utilizing information obtained pursuant to Article C.8.1.; Section F.2; or Section J.4., so that below that elevation the structure is watertight with walls substantially impermeable to passage of water;
 - b. Have structural components capable of resisting hydrostatic and hydrodynamic loads and the effects of buoyancy; and,
 - c. Be certified by a registered professional engineer or registered professional architect that the flood proofing design and methods of construction are in accordance with accepted standards of practice for meeting the provisions of this section. Such certification shall be provided with the application for a Flood Hazard Development Permit, as required by Section C.11. and shall include a record of the elevation above mean sea level to which the structure in flood proofed.
8. **Manufactured Homes** - New or substantially improved mobile homes located within Zone A shall:
 - a. Be elevated such that the lowest floor (including basement) or the manufactured home is at least one foot above the base flood elevation utilizing information obtained pursuant to Section C.8.1.; Section F.2; or Section J.4.;
 - b. Be on a permanent foundation, which may be poured masonry slab or foundation walls, with hydraulic openings, or may be reinforced piers or block supports, any of which support the manufactured home so that no weight is supported by its wheels and axles; and,

- c. Be securely anchored to an adequately anchored foundation system to resist flotation, collapse, or lateral movement. Methods of anchoring may include, but are not limited to:
 - 1. Over-the-top ties anchored to the ground at the four corners of the manufactured home, plus two additional ties per side at intermediate points (manufactured homes less than fifty feet long require one additional tie per side); or by,
 - 2. Frame ties at each corner of the home, plus five additional ties along each side at intermediate points (manufactured homes less than fifty feet long require four additional ties per side).
 - 3. All components of the anchoring system described in Section G.8.C.1 & B. shall be capable of carrying a force of 4,800 pounds.
- 9. **Accessory Structures** – Accessory Structures, as defined in Section 0, located within Zone A, shall be exempt from the elevation criteria required in Section G.6 & 7 above, if all other requirements of Section G and all the following requirements are met. Accessory Structures shall:
 - a. Be 500 square feet or less and have a value less than \$3000;
 - b. Have unfinished interiors and not be used for human habitation;
 - c. Have hydraulic openings, as specified in Section G.11.B., in at least two different walls of the accessory structure;
 - d. Be located outside the floodway;
 - e. When possible be constructed and placed on the building site to offer the minimum resistance to the flow of floodwaters and be placed further from the source of flooding than is primary structure; and,
 - f. Have only ground fault interrupt electrical outlets. The electric service disconnect shall be located above the base flood elevation and when possible outside the Special Flood Hazard Area.
- 10. **Floodways** - Encroachments, including fill, new construction, substantial improvement, and other development shall not be permitted in a floodway, which in Zone A riverine areas, is the channel of the river or other water course and the adjacent land areas to a distance of one-half the width of the floodplain as measured from the normal high-water mark to the upland limit of the floodplain, unless a technical evaluation certified by a registered professional engineer is provided demonstrating that the cumulative effect of the proposed development, when combined with all other existing development and

anticipated development:

1. Will not increase the water surface elevation of the base flood more than one foot at any point within the community; and,
2. Is consistent with the technical criteria contained in Chapter 5 entitled "Hydraulic Analyses", *Flood Insurance Study - Guidelines and Specifications for Study Contractors*, (FEMA 37/January 1195, as amended).

11. Enclosed Areas Below the Lowest Floor - New construction or substantial improvement of any structure in Zone A that meets the development standards of Section G, including the elevation requirements of Section G, paragraphs 6, 7 and 8 and is elevated on posts, columns, piers, piles, "stilts", or crawl spaces may be enclosed below the base flood elevation requirements provided all the following criteria are met or exceeded:

- a. Enclosed areas are not "basements" as defined in Section E;
- b. Enclosed areas shall be designed to automatically equalize hydrostatic flood forces on exterior walls by allowing for the entry and exit of floodwater. Designs for meeting this requirement must either:
 1. Be engineered or certified by a registered professional engineer or architect; or,
 2. Meet or exceed the following minimum criteria:
 - (a) A minimum of two openings having a total net area of not less than one square inch for every square foot of the enclosed area;
 - (b) The bottom of all openings shall be no higher than one foot above the lowest grade; and,
 - (c) Openings may be equipped with screens, louvers, valves, or other coverings or devices if they permit the entry and exit of flood waters automatically without any external influence or control such as human intervention, including the use of electrical and other non-automatic mechanical means;
3. The enclosed area shall not be used for human habitation; and,
4. The enclosed areas usable solely for building access, parking vehicles, or storage.

12. Bridges – New construction or substantial improvement of any bridge in Zone A shall be designed such that:

- A. When possible the lowest horizontal member (excluding the pilings or columns) is elevated to at least one foot above the base flood elevation utilizing information obtained pursuant to Section C.8.A.; Section F.2; or Section J.4.; and
- B. A registered professional engineer shall certify that:
 - (1) The structure design and methods of construction shall meet the elevation requirements of this section and the floodway standards of Section G.10.; and
 - (2) The foundation and superstructure attached thereto are designed to resist flotation, collapse and lateral movement because of wind and water loads acting simultaneously on all structural components. Water loading values used shall be those associated with the base flood.

13. Containment Walls – New construction or substantial improvement of any containment wall located with Zone A shall:

- A. Have the containment wall elevated to at least one foot above the base flood elevation utilizing information obtained pursuant to Section C.8.A.; Section F.2.; or Section J.4.
- B. Have structural components capable of resisting hydrostatic and hydrodynamic loads and the effects of buoyancy; and
- C. Be certified by a registered professional engineer or registered professional architect that the design and methods of construction are in accordance with accepted standards of practice for meeting the provisions of this Section. Such certification shall be provided with the application for a Flood Hazard Development Permit, as required by Section C.11.

14. Wharves, Piers and Docks - New construction or substantial improvement of wharves, piers and docks are permitted in Zone A in and over water and seaward of the mean high tide if the following requirements are met:

- A. Wharves, piers and docks shall comply with all applicable local, state and federal regulations and
- B. For commercial wharves, piers and docks, a registered professional engineer shall develop or review the structural design, specifications and plans for construction.

15. Coastal Floodplains

- A. All new construction located within Zone A shall be located landward of the reach of mean high tide except as provided in Section G.15.B.
- B. Conditional Use – Lobster sheds and fishing sheds may be located seaward of mean high tide and shall be exempt from the elevation requirement in Section G.7. only if permitted as a Conditional Use following review and approval by the Planning Board, as provided in Section H, and if all the following requirements and those of Section G.1., G.10., and G.11 are met:
 - 1. The conditional use shall be limited to low value structures such as metal or woodsheds 200 square feet or less and shall not exceed more than one story.
 - 2. The structure shall be securely anchored to the wharf or pier to resist floatation, collapse and lateral movement due to effect of wind and water loads acting simultaneously on all building components.
 - 3. The structure will not adversely increase wave or debris impact forces affecting nearby buildings.
 - 4. The structure shall have unfinished interiors and shall not be used for human habitation.
 - 5. Any mechanical, utility equipment and fuel storage tanks must be anchored and either elevated or flood proofed to one foot above the base flood elevation.
 - 6. All electrical outlets shall be grounded fault interrupt type. The electrical serve disconnect shall be located on shore above the base flood elevation and when possible outside the Special Flood Hazard Area.

H. CONDITIONAL USE REVIEW

The Planning Board shall hear and decide upon applications for conditional uses provided for in this ordinance. The Planning Board shall hear and approve, approve with conditions or disapprove all applications for conditional uses. An applicant informed by the Code Enforcement Officer that a Conditional Use Permit is required shall file an application for the permit with the Planning Board.

- 1. Review Procedure for a Conditional Use Flood hazard Development Permit
 - A. The Flood Hazard Development Permit Application with additional information attached addressing how each of the conditional use criteria

specified in the ordinance will be satisfied, may serve as the permit application for the Conditional Use permit.

- B. Before deciding any application, the Planning Board shall hold a public hearing on the application within thirty days of their receipt of the application.
- C. If the Planning Board finds that the application satisfies all relevant requirements of the ordinance, the Planning Board must approve the application or approve with conditions within 45 days of the date of the public hearing.
- D. A Conditional Use permit issued under the provisions of this ordinance shall expire if the work or change involved is not commenced within 180 days of the issuance of the permit by the Planning Board.
- E. The applicant shall be notified by the Planning Board in writing over the signature of the Chairman of the Planning Board that flood insurance is not available for structures located entirely over water or seaward of mean high tide.

2. Expansion of Conditional Uses

- A. No existing building or use of premises may be expanded or enlarged without a permit issued under this section if that building or use was established or constructed under a previously issued Conditional Use Permit or if it is a building or use which would require a Conditional Use Permit if being newly-established or constructed under this ordinance.

I. CERTIFICATE OF COMPLIANCE

No land in a special flood hazard area shall be occupied or used and no structure which is constructed or substantially improved shall be occupied until a Certificate of Compliance is issued by the Code Enforcement Officer subject to the following provisions:

- 1. For New Construction or Substantial Improvement of any elevated structure the applicant shall submit to the Code Enforcement Officer, an Elevation Certificate completed by a Professional Land Surveyor, registered professional engineer or registered professional architect, for compliance with Section G, paragraphs 6, 7 or 8.
- 2. The applicant shall submit in written notification to the Code Enforcement Officer that the development is complete and complies with the provisions of this ordinance.
- 3. Within ten working days the Code Enforcement Officer shall:

- A. Review the Elevation Certificate and the applicant's written notification; and,
- B. Upon determination that the development conforms with the provisions of this ordinance shall issue a Certificate of Compliance.

J. REVIEW OF SUBDIVISION AND DEVELOPMENT PROPSALS

The Planning Board shall, when reviewing subdivisions and other proposed developments that require review under other federal law, state law or local ordinance or regulations and all projects of 5 or more disturbed acres, or in the case of manufactured home parks divided into two or more lots, assure that:

1. All such proposals are consistent with the need to minimize flood damage.
2. All public utilities and facilities, such as sewer, gas, electrical and water systems are located and constructed to minimize or eliminate flood damages.
3. Adequate drainage is provided so as to reduce exposure to flood hazards.
4. All proposals include base flood elevations, flood boundaries and in a Riverine floodplain, floodway data. These determinations shall be based on engineering practices recognized by the Federal Emergency Management Agency.
5. Any proposed development plan must include a condition of plan approval requiring that structures on any lot in the development having any portion of its land area within a Special Flood Hazard Area, are to be constructed in accordance with Section G of this ordinance. Such requirement will be included in any deed, lease, purchase and sale agreement, or document transferring or expressing and intent to transfer any interest in real estate or structure, included but no limited to a time-share interest. The condition shall clearly articulate that the municipality may enforce any violation of the construction requirement and that fact shall also be included in the deed or any other document previously described. The construction requirement shall also be clearly stated on any map, plat or plan to be signed by the Planning Board or local reviewing authority as part of the approval process.

K. APPEALS AND VARIANCES

The Board of Appeals of the Town of Newcastle may, upon written application of an aggrieved party, hear and decide appeals where it is alleged that there is an error in any order, requirement, decision, or determination made by, or failure to act by, the Code Enforcement Officer or Planning Board in the administration or enforcement of the provisions of this ordinance.

The Board of Appeals may grant a variance from the requirements of this ordinance consistent with state law and the following criteria:

Approved: November 3, 2020

Effective: January 1, 2021

1. Variance shall not be granted within any designated regulatory floodway if any increase in flood levels during the base flood discharge would result.
2. A variance shall be granted only upon:
 - a. A showing of good and sufficient cause; and
 - b. A determination that should a flood comparable to the base flood occur, the granting of a variance will not result in increased flood heights, additional threats to public safety, public expense, or create nuisances, cause fraud or victimization of the public or conflict with existing local laws or ordinances; and,
 - c. A showing that the existence of the variance will not cause a conflict with other state, federal or local laws or ordinances; and
 - d. A determination that failure to grant the variance would result in "undue hardship", which in this subsection means:
 - (1) That the land in question cannot yield a reasonable return unless a variance is granted; and,
 - (2) That the need for a variance is due to the unique circumstances of the property and not to the general conditions in the neighborhood; and,
 - (3) That the granting of a variance will not alter the essential character of the locality; and,
 - (4) That the hardship is not the result of action taken by the applicant or a prior owner.
3. Variances shall only be issued upon a determination that the variance is the minimum necessary, considering the flood hazard, to afford relief, and the Board of Appeals may impose such conditions to a variance as it deems necessary.
4. A variance may be issued for new construction, substantial improvements, or other development for the conduct of a functionally dependent use provided that:
 - a. Other criteria of Section K and Section G.10. are met; and,
 - b. The structure or other development is protected by methods that minimize flood damages during the base flood and create no additional threats to

public safety.

5. A variance may be issued for repair, reconstruction or restoration of Historic Structures upon the determination that:
 - A. The development meets the criteria of Section K, paragraphs 1 through 4 above; and,
 - B. The proposed repair, reconstruction, rehabilitation or restoration will not preclude the structure's continued designation as Historic Structure and the variance is the minimum necessary to preserve the historic character and design of the structure.
6. Any applicant who meets the criteria of Section K, paragraphs 1 through 5, shall be notified by the Board of Appeals in writing over the signature of the Chairman of the Board of Appeals that:
 - A. The issuance of a variance to construct a structure below the base flood level will result in greatly increased premium rates for flood insurance up to amounts as high as \$25.00 per \$100.00 of insurance coverage;
 - B. Such construction below the base flood level increases risks to life and property; and,
 - C. The applicant agrees in writing that the applicant is fully aware of all the risks inherent in the use of land subject to flooding, assumes those risks and agrees to indemnify and defend the municipality against any claims filed against it that are related to the applicant's decision to use land located in a floodplain and that the applicant individually releases the municipality from any claims the applicant may have against the municipality that are related to the use of land located in a floodplain.
7. Appeal Procedure for Administrative and Variance Appeals
 - A. An administrative or variance appeal may be taken to the Board of Appeals by an aggrieved party within 30 days after receipt of a written decision of the Code Enforcement Officer or Planning Board.
 - B. Upon being notified of the appeal, the Code Enforcement Officer or Planning Board, as appropriate, shall transmit to the Board of Appeals all of the papers constituting the record of the decision appealed from.
 - C. The Board of Appeals shall hold a public hearing on the appeal within 35 days of its receipt of an appeal request.
 - D. The person filing the appeal shall have the burden of proof.

- E. The Board of Appeals shall decide all appeals within 35 days after the close of the hearing and shall issue a written decision on all appeals.
- F. The Board of Appeals shall submit to the Code Enforcement Officer a report of all variance actions, including justification for the granting of the variance and an authorization for the Code Enforcement Officer to issue a Flood Hazard Development Permit, which includes any conditions to be attached to said permit.
- G. Any aggrieved party who participated as a party during the proceedings before the Board of Appeals may take and appeal to Superior Court in accordance with State laws within 45 days from the date of any decision of the Board of Appeals.

L. ENFORCEMENT AND PENALTIES

- 1. It shall be the duty of the Code Enforcement Officer to enforce the provisions of this ordinance pursuant to Title 30-A MRSA § 4452.
- 2. The penalties contained in Title 30-A MRSA § 4452 shall apply to any violation of this ordinance.
- 3. In addition to any other actions, the Code Enforcement Officer, upon determination that a violation exists, shall submit a Declaration to the Administrator of the Federal Insurance Administration requesting a denial of flood insurance. The valid declaration shall consist of:
 - A. The name of the property owner and address or legal description of the property sufficient to confirm its identity or location;
 - B. A clear and unequivocal declaration that the property is in violation of a cited State or local law, regulation, or ordinance;
 - C. A clear statement that the public body making the declaration has authority to do so and a citation to that authority;
 - D. Evidence that the property owner has been provided notice of the violation and the prospective denial of insurance; and,
 - E. A clear statement that the declaration is being submitted pursuant to Section 1316 of the National Flood Insurance Act of 1968, as amended.

M. VALIDITY AND SEVERABILITY

If any section or provision of this ordinance is declared by the courts to be invalid, such decision shall not invalidate any other section or provision of this ordinance.

N. CONFLICT WITH OTHER ORDINANCES

This ordinance shall not in any way impair or remove the necessity of compliance with any other applicable rule, ordinance, regulation, bylaw, permit or provision of law. Where this ordinance imposes a greater restriction upon the use of land, buildings or structures, the provisions of this ordinance shall control.

O. ABROGATION

This ordinance repeals and replaces any municipal ordinance previously enacted to comply with the National Flood Insurance Act of 1968 (P.L. 90-488, as amended).